



JOB NAME	
Notes	Type IN-GROUND LIGHT

FEATURES & SPECIFICATIONS

Application

Well lights are ideal for illuminating shorter flagpoles, ranging from 20' to 40'.

Construction

Compression molded, fiberglass reinforced polyester composite housing.

Finish

Color impregnated composite which will not flake or peel when scratched.

Lens

Tempered heat resistant walk over lens available in place of standard crown glass. Provided with silicone gasket grease.

Wiring

Unit furnished with potting compound and moisture absorbing pack for moisture-free installation.

Anti-Siphon Chamber

Special chamber designed to ensure no water entry passes from junction box to main housing. Units ordered with pre-wired cords are sealed at the factory for "Quick Connects".

Listing

ETL listed.

Warranty



One year warranty on the fixture and finish and 90 days on the lamp. (CMH150/U/MED/-0)

IN-GROUND LIGHT SERIES

120 Volt
IGCOMLGT03



DIMENSIONS



Re-Designed Anti-Siphon Chamber

With the increasing problem of water build-up inside the fixture, we have redesigned all of our in-ground buckets with a new anti-siphon chamber. This chamber keeps all ballast components separated from the wiring conduit. This keeps any water absorbed from the ground confined to a separate section.



ACCESSORIES



Concrete Pour Kit



Photo Cell