



Catalog Number

DL-FLKTDLED5W
Double LED Flagpole Downlighter
5 Watt LED

FEATURES & SPECIFICATIONS

Heat Sink Housing

The die cast aluminum heat sink has 12 heat dissipating fins to maintain a cool operating LED for maximum life. The fins are independently supported to allow for unobstructed airflow. The fixture is designed to efficiently perform in any mounting orientation. A chromate pretreatment is applied prior to the finishing process to ensure lasting durability. The bullet is finished with a Super Durable Powdercoat Paint with UV inhibitor to make it impervious to atmospheric elements.

Lens Assembly

A high performance flat 120° wide flood provides the most efficient optical assembly in conjunction with the LED light source. The Lens Rings are CNC fabricated from aircraft grade aluminum and the entire unit is sealed together using integral o-rings. The Lens Ring comes standard in a black finish.

Knuckle Mount

The die cast aluminum mount is secured to the heat sink by stainless steel screws and is sealed with an integral o-ring. A ½" threaded knuckle is provided standard.

LED



A 5 watt (per bullet) double-source LED Board provides 500 Lumens of Cool White light (5500K) per bullet.

Driver Box / Transformer

A standard electrical box is required for the LED driver.



DIMENSIONS



(512) 847-0010
(800) 385-5605
www.EagleMountainFlag.com

PO Box 500 • 333 FM 2325 • Wimberley, Texas 78646